

2009 BMW F 650 GS

MSRP: \$8,995.00* Destination charge (not included in MSRP): \$495



Copyright 2009 BMW of North America, LLC., Woodcliff Lake, New Jersey all rights reserved.
 *Actual price determined by dealer. Price excludes taxes, license, options and handling charge.
 Prices and specifications subject to change without notice.

Engine		Wheels and Tires	
Type	Water cooled twin cylinder 4 stroke	Front Wheel	2.50 x 19 cast aluminum
Bore x Stroke	82 mm x 75. mm	Rear Wheel	3.50 x 17 cast aluminum
Displacement	798 cc	Front Tire	110/80 x 19 tubeless
Horsepower	71 bhp @ 7000 rpm	Rear Tire	140/80 x 17 tubeless
Torque	55 lb/ft @ 4500 rpm	Dimensions	
Compression Ratio	12.0 :1	Overall Length	89.7 inches
Valve Gear	DOHC chain driven with cam followers	Overall Width	33.2 inches
Valves	2 x 32 mm intake / 2 x 27.5 mm exhaust	Wheelbase	62.0 inches
Valves / Cylinder	4	Ground Clearance	Info. Unavailable
Engine Oil Capacity	Info. Unavailable	Seat Height	32.2 inches
Engine Management	BMW Engine Controller - BMS K	Steering Angle	64.0 degrees
Fuel Requirement	Regular Unleaded	Front Wheel Trail	3.8 inches
Fuel Tank	HDPE, internal pump and internal filter	Weight - Dry	377 lbs. excluding options & accessories
Fuel Capacity	4.2 U.S. gallons	Weight - Wet	439 lbs. excluding options & accessories
Charging System	400 Watts @ 14 Volts	Maximum Load	952 lbs. GVWR
Battery	12 Volts 14 Amps/hour maintenance-free	Available Colors	
Cooling System	50/50 water/anti-freeze mix, single radiator	Code	Price
Drivetrain		695	\$N/C
Primary Drive	1:1.943	925	\$N/C
Clutch	Wet multi plate	N26	\$N/C
1st Gear Ratio	2.46:1	Available Equipment	
2nd Gear Ratio	1.75:1	499	\$175
3rd Gear Ratio	1.38:1	519	\$250
4th Gear Ratio	1.17:1	524	\$900
5th Gear Ratio	1.04:1	530	\$250
6th Gear Ratio	0.96:1	539	\$295
Final Drive System	Chain	588	\$60
Final Drive Ratio	2.41:1	603	\$395
Frame and Suspension		636	\$150
Frame	Tubular steel trellis frame	774	\$0
Front Suspension	43 mm telescopic fork		
Front Travel	7.1 inches		
Rear Suspension	Double sided aluminum swingarm		
Rear Travel	6.7 inches		
Brakes			
Brake System	Front and rear disc with optional ABS		
Front Brakes	One double piston floating caliper		
Front Rotor	11.8 inch single rotor		
Rear Brake	One single piston floating caliper		
Rear Rotor	10.4 inch two piston floating caliper		
Actuation Method	Hydraulic, DOT 4 fluid type		